

Parameter Files Provided by VAX/VMS

File Name	Intended Hardware Configuration
MINIMUM.PAR	Minimum hardware configuration; includes only the console terminal, console floppy diskette drive, and the bootstrap disk
8USER.PAR	256K bytes of memory, 8 DZ11 lines, and 2 RK07 disk drives
16USER.PAR	512K bytes of memory, 16 DZ11 lines, 2 RM03 disk drives, line printer, TE16 magnetic tape unit
32USER.PAR	1024K bytes of memory, 32 DZ11 lines, 2 RP06 disk drives, line printer, 2 TE16 magnetic tape units, DMC-11 with DECnet-VAX
48USER.PAR	1536K bytes of memory, 48 DZ11 lines, 4 RP06 disk drives, 2 TE16 magnetic tape units, 2 RK07 disk drives, line printer, DMC-11 with DECnet-VAX
64USER.PAR	2048K bytes of memory, 64 DZ11 lines, 4 RP06 disk drives, 2 TE16 magnetic tape units, 2 RK07 disk drives, line printer, 2 DMC-11 with DECnet-VAX
VIRT32MB.PAR	1024K bytes of memory, 16 DZ11 lines, 2 RP06 disk drives, 2 TE16 magnetic tape units, line printer, and support of a 32-million byte virtual address space